

Bosch Glow Plug Attributes

New 10-DIGIT Number	Test Voltage	Pre-Heating Time (seconds)	Male Thread (D1)	SW (mm)	Tightening Torque (Nm)	Overall Length +/-0.5mm (L1)	Heating Element Length +/-0.5mm (L2)	Kind of connection D2 (mm)	Heating Element Diameter (mm) (D3)	Conical Seat (degrees)
0250202127	11	4	M10 x 1.0	10	10-15	130	32	Pin	5	93
0250212007	11	4	M14 x 1.25	10	20-35	120	21	Pin	5	123
0250203011	4.7	4	M10 x 1.25	12	10-15	136	28	M4	3	119
0250202126	11	4	M10 x 1.0	10	10-15	84	27	Pin	5	93
0250202134	11	4	M10 x 1.25	10	10-15	136	28	M4	3.4	123
0250212008	11	4	M14 x 1.25	10	20-35	121	21	Pin	5	121
0250203010	4.7	4	M10 x 1.25	12	10-15	136	28	M4	3	119
0250202133	11	4	M14 x 1.25	10	10-15	122	24	Pin	5	123
0250603010	11	< 2	M8 x 1.0	8	8-10	148	35	Pin	4	93
0250202022	11	4	M10 x 1.0	10	10-15	92	25	Pin	5	63
F01G09P2A4	11	5	M10 x 1.25	10	10-15	160	14	Pin	3.3	93
0250201039	11	4	M12 x 1.25	12	15-25	71	25	M5	6	63
0250202142	11.5	4	M10 x 1.0	10	10-15	130	28	Pin	5	63
0250403009	4.4	3	M10 x 1	10	15-20	130	28	Pin	4	63
0250403008	4.4	3	M8 x 1.0	8	8-10	148	27	Pin	3.3	93
0250201032	11	4	M12 x 1.25	12	15-25	59	21	M5	6	63
0250603009	7	<2	M10 x 1.0	10	10-15	106	33	Pin	3.2	93
0250201054	11.5	4	M12 x 1.25	12	15-25	116	28	Pin	6	63
0250001016	0.9	<20	M18 x 1.5	21	30-50	89	28	M5	10	60
0250202023	11	4	M10 x 1.0	10	10-15	97	30	Pin	5	63
0250201055	11.5	4	M12 x 1.25	12	15-25	69	23	M5	6	63
0250202008	5	<19	M10 x 1.25	12	15-20	90	24	M4	5	119
0250202054	7	<20	M10 x 1.25	12	15-20	95	31	M4	5	93
0250201036	11	4	M12 x 1.25	12	15-25	76	21	Pin	6	63
0250202089	11	4	M10 x 1.25	12	15-20	86	22	M4	5	120
0250201035	11.5	4	M12 x 1.25	12	15-25	120	28	Pin	6	63
0250202051	7	<20	M10 x 1.25	12	15-20	101	28	M4	5	93
0250202005	11	<8	M10 x 1.0	12	10-15	89	25	M4	5	119
0250202007	7	<16	M10 x 1.25	12	15-20	84	23	M4	5	119
0250201044	11	4	M18 x 1.5	21	20-30	75	29	M5	6	63
0250202073	6	<12	M10 x 1.25	12	10-15	96	32	M4	5	93
0250200055	11	< 20	M18 x 1.5	19	20-30	89	38	M5	6	60
0250201034	11	4	M12 x 1.25	12	15-25	75	30	M5	6	63
0250001010	0.9	< 20	M18 x 1.5	21	20-30	90	27	M5	9.8	60
0250202058	10.5	< 10	M10 x 1.25	12	15-20	99	28	M4	5	93
0250212014	11	< 7	M10 x 1	10	10-15	120	40	Pin	5	63
0250202097	23	30	M10 x 1.25	12	15-20	102	27	M4	5	93
0250603008	7	1.4	M8 x 1.0	8	8-10	135	28	Pin	4/3.2	93
0250603020	7	1.4	M9 x 1.0	9	6-10	156	34	Pin	4/3.2	93
0250203017	11	<4	M10 x 1.25	12	15	137	28	M4	3.5	119
F01G09P2A5	5	40	M10 x 1	10	15-20	81.4	27.7	Pin	8.4	93
0250603006	7	< 2	M10 x 1	10	10-15	134	28	Pin	7	63

sw = width across flats

